



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 20

LOCTITE 243

SDS No. : 316211
V009.9

Revision: 07.11.2019

printing date: 24.03.2020

Replaces version from: 09.07.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 243

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Tetramethylene dimethacrylate

| | |
|--|--|
| | maleic acid |
| | Acetic acid, 2-phenylhydrazide |
| Signal word: | Warning |
| Hazard statement: | H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects. |
| Precautionary statement: | "***" ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements*** |
| Precautionary statement: Prevention | P273 Avoid release to the environment. P280 Wear protective gloves. |
| Precautionary statement: Response | P333+P313 If skin irritation or rash occurs: Get medical advice/attention. |

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Anaerobic adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. | EC Number REACH-Reg No. | content | Classification |
|---|------------------------------------|----------------|--|
| Tetramethylene dimethacrylate 2082-81-7 | 218-218-1 01-2119967415-30 | 25- 50 % | Skin Sens. 1B H317 |
| 2,4,6-Triallyloxy-s-triazine 101-37-1 | 202-936-7 01-2119489756-17 | 5- < 10 % | Acute Tox. 4; Oral H302 Aquatic Chronic 2 H411 |
| 2-[[2,2-bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | 302-434-9 01-2119977121-41 | 1- < 5 % | Eye Irrit. 2 H319 Aquatic Chronic 2 H411 |
| Fatty acid amide 126098-16-6 | 484-050-2 01-0000020228-74 | 0,25- < 2,5 % | Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10 M factor (Chron Aquat Tox): 10 |
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | 201-254-7 01-2119475796-19 | 0,1- < 1 % | Acute Tox. 4; Dermal H312 STOT RE 2 H373 Acute Tox. 4; Oral H302 Org. Perox. E H242 Acute Tox. 3; Inhalation H331 Aquatic Chronic 2 H411 Skin Corr. 1B H314 |
| Acetic acid, 2-phenylhydrazide 114-83-0 | 204-055-3 | 0,1- < 1 % | Acute Tox. 3; Oral H301 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3; Inhalation H335 Carc. 2 H351 |
| maleic acid 110-16-7 | 203-742-5 01-2119488705-25 | 0,1- < 1 % | Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3 H335 |
| 1,4-Naphthalenedione 130-15-4 | 204-977-6 | 0,01- < 0,1 % | Acute Tox. 3; Oral H301 Skin Irrit. 2; Dermal H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 Acute Tox. 1; Inhalation H330 STOT SE 3; Inhalation H335 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10 M factor (Chron Aquat Tox): 10 |

**For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Fine water spray

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Use only in well-ventilated areas.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Refer to Technical Data Sheet

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|--|-----|-------------------|------------------------------|--|-----------------|
| Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [SILICA, AMORPHOUS, RESPIRABLE DUST] | | 2,4 | Time Weighted Average (TWA): | | EH40 WEL |
| Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [SILICA, AMORPHOUS, INHALABLE DUST] | | 6 | Time Weighted Average (TWA): | | EH40 WEL |
| Ethene, homopolymer 9002-88-4 [DUST, INHALABLE DUST] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Ethene, homopolymer 9002-88-4 [DUST, RESPIRABLE DUST] | | 4 | Time Weighted Average (TWA): | | EH40 WEL |
| Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, PARTICULATES] | | 10 | Time Weighted Average (TWA): | | EH40 WEL |
| Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, TOTAL VAPOUR AND PARTICULATES] | 150 | 474 | Time Weighted Average (TWA): | | EH40 WEL |

Occupational Exposure Limits

Valid for
Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|------------------------------|--|-----------------|
| Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [SILICA, AMORPHOUS, TOTAL INHALABLE DUST] | | 6 | Time Weighted Average (TWA): | | IR_OEL |
| Silane, dichlorodimethyl-, reaction products with silica 68611-44-9 [SILICA, AMORPHOUS, RESPIRABLE DUST] | | 2,4 | Time Weighted Average (TWA): | | IR_OEL |
| Ethene, homopolymer 9002-88-4 [DUSTS, NON-SPECIFIC, RESPIRABLE] | | 4 | Time Weighted Average (TWA): | | IR_OEL |
| Ethene, homopolymer 9002-88-4 [DUSTS, NON-SPECIFIC, TOTAL INHALABLE] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, PARTICULATES] | | 10 | Time Weighted Average (TWA): | | IR_OEL |
| Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, TOTAL (VAPOUR AND PARTICULATES)] | 150 | 470 | Time Weighted Average (TWA): | | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|--|---------------------------------|-----------------|---------------|-----|---------------|--------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| Tetramethylene dimethacrylate 2082-81-7 | aqua (freshwater) | | 0,043 mg/l | | | | |
| Tetramethylene dimethacrylate 2082-81-7 | aqua (marine water) | | 0,004 mg/l | | | | |
| Tetramethylene dimethacrylate 2082-81-7 | aqua (intermittent releases) | | 0,098 mg/l | | | | |
| Tetramethylene dimethacrylate 2082-81-7 | sewage treatment plant (STP) | | 2 mg/l | | | | |
| Tetramethylene dimethacrylate 2082-81-7 | sediment (freshwater) | | | | 3,12 mg/kg | | |
| Tetramethylene dimethacrylate 2082-81-7 | sediment (marine water) | | | | 0,312 mg/kg | | |
| Tetramethylene dimethacrylate 2082-81-7 | Soil | | | | 0,573 mg/kg | | |
| 2,4,6-Triallyloxy-1,3,5-triazine 101-37-1 | aqua (freshwater) | | 0,00705 mg/l | | | | |
| 2,4,6-Triallyloxy-1,3,5-triazine 101-37-1 | aqua (marine water) | | 0,0007 mg/l | | | | |
| 2,4,6-Triallyloxy-1,3,5-triazine 101-37-1 | aqua (intermittent releases) | | 0,0705 mg/l | | | | |
| 2,4,6-Triallyloxy-1,3,5-triazine 101-37-1 | sediment (freshwater) | | | | 0,1729 mg/kg | | |
| 2,4,6-Triallyloxy-1,3,5-triazine 101-37-1 | sediment (marine water) | | | | 0,01729 mg/kg | | |
| 2,4,6-Triallyloxy-1,3,5-triazine 101-37-1 | Soil | | | | 0,057 mg/kg | | |
| 2,4,6-Triallyloxy-1,3,5-triazine 101-37-1 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| 2,4,6-Triallyloxy-1,3,5-triazine 101-37-1 | oral | | | | 0,119 mg/kg | | |
| 2-[[2,2-Bis[(1-oxoallyl)oxy)methyl]butoxy)methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | aqua (freshwater) | | 0,0012 mg/l | | | | |
| 2-[[2,2-Bis[(1-oxoallyl)oxy)methyl]butoxy)methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | Soil | | | | 0,096 mg/kg | | |
| 2-[[2,2-Bis[(1-oxoallyl)oxy)methyl]butoxy)methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | sediment (marine water) | | | | 0,048 mg/kg | | |
| 2-[[2,2-Bis[(1-oxoallyl)oxy)methyl]butoxy)methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | sediment (freshwater) | | | | 0,484 mg/kg | | |
| 2-[[2,2-Bis[(1-oxoallyl)oxy)methyl]butoxy)methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | sewage treatment plant (STP) | | 100 mg/l | | | | |
| 2-[[2,2-Bis[(1-oxoallyl)oxy)methyl]butoxy)methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | aqua (intermittent releases) | | 0,012 mg/l | | | | |
| 2-[[2,2-Bis[(1-oxoallyl)oxy)methyl]butoxy)methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | aqua (marine water) | | 0,00012 mg/l | | | | |
| Fatty acid amide 126098-16-6 | aqua (freshwater) | | 0,000146 mg/l | | | | |
| Fatty acid amide 126098-16-6 | aqua (marine water) | | 0,0146 g/l | | | | |
| Fatty acid amide 126098-16-6 | aqua (intermittent releases) | | 0,00025 mg/l | | | | |
| Fatty acid amide | sediment | | | | 5,554 | | |

| | | | | | | | |
|--|------------------------------------|--|-----------------|--|-----------------|--|--|
| 126098-16-6 | (marine water) | | | | mg/kg | | |
| Fatty acid amide 126098-16-6 | aqua (freshwater) | | | | 55,54 mg/kg | | |
| Fatty acid amide 126098-16-6 | Soil | | | | 66,576 mg/kg | | |
| Fatty acid amide 126098-16-6 | sewage treatment plant (STP) | | 10 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (freshwater) | | 0,0031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (marine water) | | 0,00031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | aqua (intermittent releases) | | 0,031 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Sewage treatment plant | | 0,35 mg/l | | | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sediment (freshwater) | | | | 0,023 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | sediment (marine water) | | | | 0,0023 mg/kg | | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Soil | | | | 0,0029 mg/kg | | |
| Maleic acid 110-16-7 | aqua (freshwater) | | 0,1 mg/l | | | | |
| Maleic acid 110-16-7 | aqua (intermittent releases) | | 0,4281 mg/l | | | | |
| Maleic acid 110-16-7 | sediment (freshwater) | | | | 0,334 mg/kg | | |
| Maleic acid 110-16-7 | sewage treatment plant (STP) | | 44,6 mg/l | | | | |
| Maleic acid 110-16-7 | aqua (marine water) | | 0,01 mg/l | | | | |
| Maleic acid 110-16-7 | sediment (marine water) | | | | 0,0334 mg/kg | | |
| Maleic acid 110-16-7 | Soil | | | | 0,0415 mg/kg | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|--|--------------------|-------------------|--|---------------|-------------------------|---------|
| Tetramethylene dimethacrylate 2082-81-7 | Workers | dermal | Long term exposure - systemic effects | | 4,2 mg/kg | |
| Tetramethylene dimethacrylate 2082-81-7 | Workers | inhalation | Long term exposure - systemic effects | | 14,5 mg/m ³ | |
| Tetramethylene dimethacrylate 2082-81-7 | General population | inhalation | Long term exposure - systemic effects | | 4,3 mg/m ³ | |
| Tetramethylene dimethacrylate 2082-81-7 | General population | dermal | Long term exposure - systemic effects | | 2,5 mg/kg | |
| Tetramethylene dimethacrylate 2082-81-7 | General population | oral | Long term exposure - systemic effects | | 2,5 mg/kg | |
| 2,4,6-Triallyloxy-1,3,5-triazine 101-37-1 | Workers | inhalation | Acute/short term exposure - systemic effects | | 134,4 mg/m ³ | |
| 2,4,6-Triallyloxy-1,3,5-triazine 101-37-1 | Workers | dermal | Long term exposure - systemic effects | | 1,5 mg/kg | |
| 2,4,6-Triallyloxy-1,3,5-triazine 101-37-1 | Workers | inhalation | Long term exposure - systemic effects | | 2,12 mg/m ³ | |
| 2-[[2,2-Bis[[[1-(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | Workers | Inhalation | Long term exposure - systemic effects | | 5,88 mg/m ³ | |
| 2-[[2,2-Bis[[[1-(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | Workers | dermal | Long term exposure - systemic effects | | 1,67 mg/kg | |
| Fatty acid amide 126098-16-6 | General population | oral | Long term exposure - systemic effects | | 8,3 mg/kg | |
| Fatty acid amide 126098-16-6 | General population | dermal | Long term exposure - systemic effects | | 8,3 mg/kg | |
| Fatty acid amide 126098-16-6 | Workers | dermal | Long term exposure - systemic effects | | 14 mg/kg | |
| Fatty acid amide 126098-16-6 | General population | inhalation | Long term exposure - systemic effects | | 2,9 mg/m ³ | |
| Fatty acid amide 126098-16-6 | Workers | inhalation | Long term exposure - systemic effects | | 9,8 mg/m ³ | |
| .alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9 | Workers | inhalation | Long term exposure - systemic effects | | 6 mg/m ³ | |
| Maleic acid 110-16-7 | Workers | dermal | Acute/short term exposure - local effects | | 0,55 mg/cm ² | |
| Maleic acid 110-16-7 | Workers | dermal | Long term exposure - local effects | | 0,04 mg/cm ² | |
| Maleic acid 110-16-7 | Workers | dermal | Acute/short term exposure - systemic effects | | 58 mg/kg | |
| Maleic acid 110-16-7 | Workers | dermal | Long term exposure - systemic effects | | 3,3 mg/kg | |
| Maleic acid 110-16-7 | Workers | inhalation | Acute/short term exposure - local effects | | 3 mg/m ³ | |
| Maleic acid 110-16-7 | Workers | inhalation | Long term exposure - systemic effects | | 3 mg/m ³ | |
| Maleic acid 110-16-7 | Workers | inhalation | Long term exposure - local effects | | 3 mg/m ³ | |

| | | | | |
|-------------------------|---------|------------|--|---------|
| Maleic acid 110-16-7 | Workers | inhalation | Acute/short term exposure - systemic effects | 3 mg/m3 |
|-------------------------|---------|------------|--|---------|

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|----------------------------|------------------------------------|
| Appearance | liquid blue |
| Odor | characteristic |
| Odour threshold | No data available / Not applicable |
| pH | No data available / Not applicable |
| Melting point | No data available / Not applicable |
| Solidification temperature | No data available / Not applicable |
| Initial boiling point | No data available / Not applicable |
| Flash point | > 93 °C (> 199.4 °F) |
| Evaporation rate | No data available / Not applicable |
| Flammability | No data available / Not applicable |
| Explosive limits | No data available / Not applicable |
| Vapour pressure | 1,7 mbar |

| | |
|--|------------------------------------|
| (25 °C (77 °F)) | |
| Vapour pressure | < 300 mbar |
| (50 °C (122 °F)) | |
| Relative vapour density: | No data available / Not applicable |
| Density | 1,08 g/cm ³ |
| () | |
| Bulk density | No data available / Not applicable |
| Solubility | No data available / Not applicable |
| Solubility (qualitative) | Insoluble |
| (Solvent: Water) | |
| Solubility (qualitative) | Soluble |
| (Solvent: Acetone) | |
| Partition coefficient: n-octanol/water | No data available / Not applicable |
| Auto-ignition temperature | No data available / Not applicable |
| Decomposition temperature | No data available / Not applicable |
| Viscosity | No data available / Not applicable |
| Viscosity (kinematic) | No data available / Not applicable |
| Explosive properties | No data available / Not applicable |
| Oxidising properties | No data available / Not applicable |

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Peroxides.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

General toxicological information:

Prolonged or repeated contact may cause eye irritation.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|---------------|---------|---|
| Tetramethylene dimethacrylate 2082-81-7 | LD50 | 10.066 mg/kg | rat | equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) |
| 2,4,6-Triallyloxy-s-triazine 101-37-1 | LD50 | 753 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| 2-[[2,2-bis[[1-(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | LD50 | > 5.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Fatty acid amide 126098-16-6 | LD50 | > 2.000 mg/kg | rat | not specified |
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | LD50 | 382 mg/kg | rat | other guideline: |
| Acetic acid, 2-phenylhydrazide 114-83-0 | LD50 | 270 mg/kg | rat | not specified |
| maleic acid 110-16-7 | LD50 | 708 mg/kg | rat | not specified |
| 1,4-Naphthalenedione 130-15-4 | LD50 | 190 mg/kg | rat | not specified |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|-------------------------------|-------------------|---------|--|
| Tetramethylene dimethacrylate 2082-81-7 | LD50 | > 3.000 mg/kg | rabbit | not specified |
| 2,4,6-Triallyloxy-s-triazine 101-37-1 | LD50 | > 2.000 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |
| 2-[[2,2-bis[[1-(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | LD50 | > 2.000 mg/kg | rat | not specified |
| Fatty acid amide 126098-16-6 | LD50 | > 2.000 mg/kg | rat | not specified |
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | LD50 | 530 - 1.060 mg/kg | rat | other guideline: |
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | Acute toxicity estimate (ATE) | 1.100 mg/kg | | Expert judgement |
| maleic acid 110-16-7 | LD50 | 1.560 mg/kg | rabbit | not specified |

Acute inhalative toxicity:

No substance data available.
No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|--|------------|------------------|---------|-------------|
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | corrosive | | rabbit | Draize Test |
| maleic acid 110-16-7 | irritating | 24 h | human | Patch Test |

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|---|----------------------|------------------|---------|--|
| 2-[[2,2-bis[[1-(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | Category II | | rabbit | EU Method B.5 (Acute Toxicity: Eye Irritation / Corrosion) |
| maleic acid 110-16-7 | highly irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|--|-------------|------------------------------------|------------|---|
| Tetramethylene dimethacrylate 2082-81-7 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| maleic acid 110-16-7 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |
| maleic acid 110-16-7 | sensitising | Mouse local lymphnode assay (LLNA) | guinea pig | OECD Guideline 406 (Skin Sensitisation) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|--|----------|--|--|---------|--|
| Tetramethylene dimethacrylate 2082-81-7 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Tetramethylene dimethacrylate 2082-81-7 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Tetramethylene dimethacrylate 2082-81-7 | positive | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | positive | bacterial reverse mutation assay (e.g Ames test) | without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| maleic acid 110-16-7 | negative | bacterial reverse mutation assay (e.g Ames test) | no data | | Ames Test |
| maleic acid 110-16-7 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|------------------------------|------------------|----------------------|--|---------|-------------|---|
| maleic acid 110-16-7 | not carcinogenic | oral: feed | 2 y daily | rat | male/female | OECD Guideline 451 (Carcinogenicity Studies) |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|------------------------------|---|----------------------|----------------------|---------|---|
| maleic acid 110-16-7 | NOAEL F1 150 mg/kg NOAEL F2 55 mg/kg | Two generation study | oral: gavage | rat | OECD Guideline 416 (Two-Generation Reproduction Toxicity Study) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|--|-----------------------|------------------------|--|---------|---|
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | | inhalation: aerosol | 6 h/d 5 d/w | rat | not specified |
| maleic acid 110-16-7 | NOAEL \geq 40 mg/kg | oral: feed | 90 d daily | rat | OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|------------|---------------|---------------------|--|
| Tetramethylene dimethacrylate 2082-81-7 | LC50 | 32,5 mg/l | 48 h | | DIN 38412-15 |
| 2,4,6-Triallyloxy-s-triazine 101-37-1 | LC50 | 4,36 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| 2-[[2,2-bis[(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | LC50 | 1,2 mg/l | 96 h | Cyprinus carpio | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Fatty acid amide 126098-16-6 | LC50 | | 96 h | Cyprinus carpio | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | LC50 | 3,9 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| maleic acid 110-16-7 | LC50 | > 245 mg/l | 48 h | Leuciscus idus | DIN 38412-15 |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|------------|---------------|---------------|--|
| 2,4,6-Triallyloxy-s-triazine 101-37-1 | EC50 | 19,4 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| 2-[[2,2-bis[(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | EC50 | > 10 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Fatty acid amide 126098-16-6 | EC50 | | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | EC50 | 18 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| maleic acid 110-16-7 | EC50 | 42,81 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|-----------|---------------|---------------|---|
| Tetramethylene dimethacrylate 2082-81-7 | NOEC | 5,09 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Fatty acid amide 126098-16-6 | NOEC | | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| maleic acid 110-16-7 | NOEC | 10 mg/l | 21 d | Daphnia magna | other guideline: |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|-------------|---------------|---------------------------------|---|
| Tetramethylene dimethacrylate 2082-81-7 | EC50 | 9,79 mg/l | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Tetramethylene dimethacrylate 2082-81-7 | NOEC | 2,11 mg/l | 72 h | Desmodesmus subspicatus | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2-[[2,2-bis[[1-(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | EC50 | > 12 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 2-[[2,2-bis[[1-(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | NOEC | < 0,35 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Fatty acid amide 126098-16-6 | EC50 | 0,025 mg/l | 72 h | not specified | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Fatty acid amide 126098-16-6 | NOEC | 0,0073 mg/l | 72 h | not specified | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | ErC50 | 3,1 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| maleic acid 110-16-7 | EC50 | 74,35 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| maleic acid 110-16-7 | EC10 | 11,8 mg/l | 72 h | Pseudokirchneriella subcapitata | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| 1,4-Naphthalenedione 130-15-4 | EC50 | 0,011 mg/l | 72 h | Dunaliella bioculata | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|--|---------------|-----------|---------------|---|--|
| Tetramethylene dimethacrylate 2082-81-7 | NOEC | 20 mg/l | 28 d | activated sludge, domestic | not specified |
| 2,4,6-Triallyloxy-s-triazine 101-37-1 | EC0 | 5 mg/l | 3 h | | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| Fatty acid amide 126098-16-6 | EC50 | | 3 h | activated sludge of a predominantly domestic sewage | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | EC10 | 70 mg/l | 30 min | | not specified |
| maleic acid 110-16-7 | EC10 | 44,6 mg/l | 18 h | Pseudomonas putida | DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test) |

12.2. Persistence and degradability

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|---|----------------------------|-----------|---------------|------------------|--|
| Tetramethylene dimethacrylate 2082-81-7 | readily biodegradable | aerobic | 84 % | 28 d | OECD Guideline 310 (Ready Biodegradability CO2 in Sealed Vessels (Headspace Test)) |
| 2,4,6-Triallyloxy-s-triazine 101-37-1 | | aerobic | 7 - 9 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| 2-[[2,2-bis[[[1-oxoallyl]oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | | aerobic | 4 - 14 % | 29 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| Fatty acid amide 126098-16-6 | not readily biodegradable. | aerobic | 7 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | | no data | 0 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| maleic acid 110-16-7 | readily biodegradable | aerobic | 97,08 % | 28 d | OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test) |
| 1,4-Naphthalenedione 130-15-4 | not readily biodegradable. | no data | 0 - 60 % | | OECD 301 A - F |

12.3. Bioaccumulative potential

| Hazardous substances CAS-No. | Bioconcentration factor (BCF) | Exposure time | Temperature | Species | Method |
|--|-------------------------------|---------------|-------------|-------------|---|
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | 9,1 | | | calculation | OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) |

12.4. Mobility in soil

Cured adhesives are immobile.

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---|--------|-------------|--|
| Tetramethylene dimethacrylate 2082-81-7 | 3,1 | | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| 2,4,6-Triallyloxy-s-triazine 101-37-1 | 2,8 | 20 °C | not specified |
| 2-[[2,2-bis[[1-(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | 4,14 | 30 °C | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| Fatty acid amide 126098-16-6 | > 6,5 | 20 °C | OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method) |
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | 2,16 | | not specified |
| Acetic acid, 2-phenylhydrazide 114-83-0 | 0,74 | | not specified |
| maleic acid 110-16-7 | -1,3 | 20 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| 1,4-Naphthalenedione 130-15-4 | 1,71 | | not specified |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT / vPvB |
|---|---|
| Tetramethylene dimethacrylate 2082-81-7 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 2,4,6-Triallyloxy-s-triazine 101-37-1 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 2-[[2,2-bis[[1-(1-oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-1,3-propanediyl diacrylate 94108-97-1 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Fatty acid amide 126098-16-6 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| α , α -dimethylbenzyl hydroperoxide 80-15-9 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| maleic acid 110-16-7 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| 1,4-Naphthalenedione 130-15-4 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Collection and delivery to recycling enterprise or other registered elimination institution.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

| |
|--|
| SECTION 14: Transport information |
|--|

14.1. UN number

| | |
|------|------|
| ADR | 3082 |
| RID | 3082 |
| ADN | 3082 |
| IMDG | 3082 |
| IATA | 3082 |

14.2. UN proper shipping name

| | |
|------|--|
| ADR | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide) |
| RID | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide) |
| ADN | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide) |
| IMDG | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide) |
| IATA | Environmentally hazardous substance, liquid, n.o.s. (Fatty acid amide) |

14.3. Transport hazard class(es)

| | |
|------|---|
| ADR | 9 |
| RID | 9 |
| ADN | 9 |
| IMDG | 9 |
| IATA | 9 |

14.4. Packing group

| | |
|------|-----|
| ADR | III |
| RID | III |
| ADN | III |
| IMDG | III |
| IATA | III |

14.5. Environmental hazards

| | |
|------|------------------|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | Marine pollutant |
| IATA | not applicable |

14.6. Special precautions for user

| | |
|------|-------------------------------|
| ADR | not applicable Tunnelcode: |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content < 3 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H242 Heating may cause a fire.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.