

Permabond®

Engineering Adhesives

SAFETY DATA SHEET

Permabond TA4210A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permabond TA4210A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Permabond Engineering Adhesives Ltd.
Wessex Way
Colden Common
Winchester
Hampshire SO21 1WP
United Kingdom
Tel: +44 (0)1962 711 661
Fax: +44 (0)1962 711 662
info.europe@permabond.com

1.4. Emergency telephone number

Emergency telephone CHEMTREC UK: +(44)-870-8200418 CHEMTREC US: 800-424-9300 (CCN: 829878)

National emergency telephone number CHEMTREC Ireland: +(353)-19014670
CHEMTREC Australia: +(61)-290372994
CHEMTREC New Zealand: +(64)-98010034

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

Permabond TA4210A

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352a IF ON SKIN: Wash with plenty of soap and water</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308+P313 IF exposed or concerned: Get medical advice/ attention.</p>
Supplemental label information	EUH205 Contains epoxy constituents. May produce an allergic reaction.
Contains	METHYL METHACRYLATE, EPOXY RESIN (Number average MW <= 700), METHACRYLIC ACID, CUMENE HYDROPEROXIDE
Supplementary precautionary statements	<p>P243 Take action to prevent static discharges.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/container in accordance with existing Community, National and local regulations.</p>

2.3. Other hazards

None under normal conditions. This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

METHYL METHACRYLATE 60-100% CAS number: 80-62-6 EC number: 201-297-1 REACH registration number: 01-2119452498-28-XXXX
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Skin Sens. 1 - H317 STOT SE 3 - H335
EPOXY RESIN (Number average MW <= 700) 5-10% CAS number: 1675-54-3 EC number: 216-823-5 REACH registration number: 01-2119456619-26-XXXX
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

Permabond TA4210A

METHACRYLIC ACID	1-5%
CAS number: 79-41-4	EC number: 201-204-4
	REACH registration number: 01-2119463884-26-XXXX
Classification	
Acute Tox. 4 - H302	
Acute Tox. 3 - H311	
Acute Tox. 4 - H332	
Skin Corr. 1A - H314	
Eye Dam. 1 - H318	
STOT SE 3 - H335	
CUMENE HYDROPEROXIDE	1-< 2.5%
CAS number: 80-15-9	EC number: 201-254-7
	REACH registration number: 01-2119475796-19-XXXX
Classification	
Org. Perox. E - H242	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 3 - H331	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
STOT SE 3 - H335	
STOT RE 2 - H373	
Aquatic Chronic 2 - H411	
2,6-DI-TERT-BUTYL-P-CRESOL	1-5%
CAS number: 128-37-0	EC number: 204-881-4
M factor (Acute) = 1	M factor (Chronic) = 1
REACH registration exemption – < 1 tonne	
Classification	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. If symptoms develop, obtain medical attention
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Permabond TA4210A

Skin contact Skin irritation. Mild dermatitis, allergic skin rash.

Eye contact May cause serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Flammable liquid and vapour. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

Hazardous combustion products Burning produces irritating, toxic and obnoxious fumes. Carbon monoxide, carbon dioxide, and unknown hydrocarbons. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Eliminate all sources of ignition. Ensure adequate ventilation of the working area. Do not breathe vapour. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for disposal.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Use in a well ventilated area. Do not ingest or inhale. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep container tightly closed, in a cool, well ventilated place. Keep container dry. Store in closed original container at temperatures between 2°C and 7°C.

7.3. Specific end use(s)

Specific end use(s) Adhesive.

PermaBond TA4210A

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

METHYL METHACRYLATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³

METHACRYLIC ACID

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m³

Short-term exposure limit (15-minute): WEL 40 ppm 143 mg/m³

2,6-DI-TERT-BUTYL-P-CRESOL

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

WEL = Workplace Exposure Limit

METHYL METHACRYLATE (CAS: 80-62-6)

DNEL	Workers, Industry/Professional - Inhalation; Long term : 208 mg/m ³ Workers, Industry/Professional - Dermal; Long term : 13.67 mg/kg/day Workers, Industry/Professional - Inhalation; Short term : 416 mg/m ³
PNEC	Workers, Industry/Professional - Water; Long term <0.94 mg/l

EPOXY RESIN (Number average MW <= 700) (CAS: 1675-54-3)

DNEL	Workers - Inhalation; Long term systemic effects: 12.25 mg/m ³ Workers - Dermal; Long term systemic effects: 8.33 mg/kg/day Workers - Inhalation; Short term systemic effects: 12.25 mg/m ³ Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day
PNEC	- Fresh water; Long term 0.006 mg/l - Sediment (Freshwater); Long term 0.996 mg/l - Sediment (Marinewater); 0.0996 mg/l - STP; Long term 10 mg/l - Soil; Long term 0.196 mg/l - marine water; 0.0006 mg/l - Water; 0.0018 mg/l

METHACRYLIC ACID (CAS: 79-41-4)

DNEL	Workers, Industry - Inhalation; Long term local effects: 88 mg/m ³ Workers, Industry - Dermal; Long term systemic effects: 4.25 mg/kg/day Workers, Industry - Inhalation; Long term systemic effects: 29.6 mg/m ³
PNEC	Workers, Industry - Fresh water; 0.82 mg/l Workers, Industry - marine water; 0.82 mg/l Workers, Industry - STP; 10 mg/l Workers, Industry - Soil; 1.2 mg/kg

CUMENE HYDROPEROXIDE (CAS: 80-15-9)

DNEL	Workers - Inhalation; Long term systemic effects: 6 mg/m ³
-------------	---

Permabond TA4210A

PNEC	Workers - Fresh water; 0.0031 mg/l
	Workers - marine water; 0.00031 mg/l
	Workers - Intermittent release; 0.031 mg/l
	Workers, Industry - Soil; 1.2 mg/kg
	Workers - STP; 0.35 mg/l
	Workers - Sediment (Freshwater); 0.023 mg/kg
	Workers - Sediment (Marinewater); 0.0023 mg/kg
	Workers - Soil; 0.0029 mg/kg

2,6-DI-TERT-BUTYL-P-CRESOL (CAS: 128-37-0)

DNEL	Workers - Inhalation; Long term systemic effects: 3.5 mg/m ³
	Workers - Dermal; Long term systemic effects: 0.5 mg/kg/day
PNEC	Fresh water; 0.199 µg/l
	marine water; 0.02 µg/l
	STP; 0.17 mg/l
	Sediment (Freshwater); 99.6 µg/kg
	Sediment (Marinewater); 9.96 µg/kg
	Soil; 8.33 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Personal eye protection should conform to EN 166

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn. Gloves should conform to EN 374. For exposure up to 4 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 0.5 hours. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 8 hours. The breakthrough time for any glove material may be different for different glove manufacturers. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Other skin and body protection

Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke. Use of good industrial hygiene practices is required.

Respiratory protection

Ensure adequate ventilation of the working area. Respiratory protection may be required if excessive airborne contamination occurs. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Organic vapour filter. Type A. (EN14387)

Permabond TA4210A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	Off-white.
Odour	Pungent. Acrylic
Odour threshold	Not available.
pH	Not relevant.
Melting point	Not available.
Initial boiling point and range	~100°C
Flash point	11°C
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	≈28 mm Hg
Vapour density	≈3.46
Relative density	1.1
Solubility(ies)	Slightly soluble in water. Soluble in the following materials: Organic solvents.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Viscosity	≈45000 mPa s @ 23°C Thixotropic
Oxidising properties	Not available.
9.2. Other information	
Other information	Not relevant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react with the product: Strong oxidising agents. Strong acids. Strong alkalis.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Take precautionary measures against static discharges. Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Strong alkalis.

Permabond TA4210A

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified organic compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Skin sensitisation

Skin sensitisation May cause sensitisation by skin contact.

Aspiration hazard

Aspiration hazard None under normal conditions.

Inhalation

May cause respiratory system irritation.

Skin contact

Irritating to skin.

Eye contact

Causes serious eye damage.

Toxicological information on ingredients.

METHYL METHACRYLATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,000.0

Species Rat

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 29.8

Species Rat

Skin corrosion/irritation

Skin corrosion/irritation Not irritating. Prolonged skin contact may cause temporary irritation.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Respiratory sensitisation

Respiratory sensitisation Mouse: Sensitising.

Skin sensitisation

Permabond TA4210A

Skin sensitisation	Local Lymph Node Assay (LLNA) - Mouse: Sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Inconclusive.
Genotoxicity - in vivo	This substance has no evidence of mutagenic properties.
<u>Carcinogenicity</u>	
Carcinogenicity	CMR: no
IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No evidence of reproductive toxicity in animal studies.
Reproductive toxicity - development	No evidence of reproductive toxicity in animal studies. non-teratogenic, not embryotoxic
<u>Specific target organ toxicity - single exposure</u>	
Target organs	Respiratory tract Irritation.
<u>Specific target organ toxicity - repeated exposure</u>	
Target organs	No specific target organs known.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.

EPOXY RESIN (Number average MW <= 700)

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	11,400.0
Species	Rat
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	2,000.1
Species	Rabbit
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC₅₀)	No specific test data are available.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Not irritating.
Animal data	Oedema score: Very slight oedema - barely perceptible (1).
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Not irritating.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	No specific test data are available.
<u>Skin sensitisation</u>	

Permabond TA4210A

Skin sensitisation	Local Lymph Node Assay (LLNA) - Mouse: Sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Conclusive data but not sufficient for classification.
<u>Carcinogenicity</u>	
Carcinogenicity	Conclusive data but not sufficient for classification.
IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Fertility - NOAEL 750 mg/kg/day, Oral, Rat
Reproductive toxicity - development	Developmental toxicity: - NOAEL: 180 mg/kg/day, Oral, Rat
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	No specific test data are available.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Conclusive data but not sufficient for classification.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.

METHACRYLIC ACID

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	1,320.0
Species	Rat
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	1,000.0
Species	Rabbit
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	7.1
Species	Rat
<u>Skin corrosion/irritation</u>	
Animal data	Dose: Method: OECD 404, 3 minutes, Rabbit Corrosive.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Method: OECD 405, Rabbit Corrosive.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Guinea pig: Not sensitising. Method: various test systems
<u>Skin sensitisation</u>	

Permabond TA4210A

Skin sensitisation	Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	CMR: no
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No evidence of reproductive toxicity in animal studies.
Reproductive toxicity - development	Non-teratogenic, not embryotoxic
<u>Specific target organ toxicity - single exposure</u>	
Target organs	Respiratory tract Irritating.
<u>Specific target organ toxicity - repeated exposure</u>	
Target organs	No specific target organs known.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.

CUMENE HYDROPEROXIDE

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	328.0
Species	Rat
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	1,200.0
Species	Rat
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ dust/mist mg/l)	1.37
Species	Rat
<u>Skin corrosion/irritation</u>	
Animal data	Highly irritating.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Irritating to eyes.
<u>Skin sensitisation</u>	
Skin sensitisation	Not sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Positive.

Permabond TA4210A

Genotoxicity - in vivo	This substance has no evidence of mutagenic properties.
<u>Carcinogenicity</u>	
Carcinogenicity	CMR: No
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No specific test data are available.
Reproductive toxicity - development	Developmental toxicity: - NOAEL: ≥ 100 mg/kg/day, Oral, Rat
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	No specific test data are available.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Toxic: danger of serious damage to health by prolonged exposure through inhalation.
<u>Aspiration hazard</u>	
Aspiration hazard	No specific test data are available.

2,6-DI-TERT-BUTYL-P-CRESOL

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	6,000.0
Species	Rat
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	2,000.1
Species	Rat
<u>Skin corrosion/irritation</u>	
Animal data	Erythema/eschar score: No erythema (0). Not irritating.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Method: OECD 405, Rabbit Not irritating.
<u>Skin sensitisation</u>	
Skin sensitisation	- Guinea pig: Not sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Gene mutation: Negative.
Genotoxicity - in vivo	Chromosome aberration: Negative.
<u>Carcinogenicity</u>	
Carcinogenicity	No evidence of carcinogenicity in animal studies.
IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<u>Reproductive toxicity</u>	

Permabond TA4210A

Reproductive toxicity - fertility Two-generation study - NOAEL 100 mg/kg/day, Oral, Rat F1

Reproductive toxicity - development Developmental toxicity: - LOAEL: 500 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard No information available. No information available.

SECTION 12: Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

12.1. Toxicity

Toxicity The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Ecological information on ingredients.

METHYL METHACRYLATE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: > 79 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 69 mg/l, Daphnia magna

Acute toxicity - aquatic plants NOEC, 72 hours: > 110 mg/l, Selenastrum capricornutum
EC₅₀, 72 hours: > 100 mg/l, Selenastrum capricornutum

Acute toxicity - microorganisms EC₂₀, 30 minutes: 150 - 200 mg/l, Activated sludge

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOEC, 35 days: 9.4 mg/l, Danio rerio (Zebrafish)

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 37 mg/l, Daphnia magna

EPOXY RESIN (Number average MW <= 700)

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 24 hours: 4.4 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates LC₅₀, 24 hours: 4.9 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 48 hours: 9.1 mg/l, Selenastrum capricornutum

Permabond TA4210A

Acute toxicity - microorganisms IC₅₀, 3 hours: > 100 mg/l, Activated sludge

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 0.3 mg/l, Daphnia magna

METHACRYLIC ACID

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 85 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: > 130 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 45 mg/l, Selenastrum capricornutum
LOEC, 72 hours: 45 mg/l, Selenastrum capricornutum

Acute toxicity - microorganisms EC₅₀, 17 hours: 270 mg/l, Pseudomonas putida

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOEC, 35 days: 10 mg/l, Danio rerio (Zebrafish)

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 53 mg/l, Daphnia magna

CUMENE HYDROPEROXIDE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hour: 3.9 mg/l, Oncorhynchus mykiss (Rainbow trout)

2,6-DI-TERT-BUTYL-P-CRESOL

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

Acute toxicity - fish LC₅₀, 96 hours: 0.199 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 0.48 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 96 hours: 0.758 mg/l, Algae

Chronic aquatic toxicity

M factor (Chronic) 1

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

Ecological information on ingredients.

METHYL METHACRYLATE

Biodegradation Water - Degradation 94%: 14 days

Permabond TA4210A

EPOXY RESIN (Number average MW <= 700)

Biodegradation Water - 6 - 12%: 28 days

METHACRYLIC ACID

Biodegradation Water - Degradation 86%: 28 days

CUMENE HYDROPEROXIDE

Biodegradation The substance is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Bioaccumulative potential BCF: 100 - 3000,

Partition coefficient log Pow: 3.242

2,6-DI-TERT-BUTYL-P-CRESOL

Partition coefficient log Pow: 5.1

12.4. Mobility in soil

Mobility No data available. The product has poor water-solubility.

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Adsorption/desorption coefficient Water - log Koc: 2.65 @ 20°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste disposal should be in accordance with existing Community, National and local regulations Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances.

Permabond TA4210A

SECTION 14: Transport information

14.1. UN number

1993

14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (contains Methylmethacrylate and Methacrylic Acid)

14.3. Transport hazard class(es)

3

Transport labels



14.4. Packing group

II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-E

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Guidance Workplace Exposure Limits EH40.
CHIP for everyone HSG228.
Safety Data Sheets for Substances and Preparations.
Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Permabond TA4210A

Revision date	25/02/2019
Revision	6
Supersedes date	30/06/2017
Hazard statements in full	<p>H225 Highly flammable liquid and vapour. H242 Heating may cause a fire. H302 Harmful if swallowed. H311 Toxic in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Permabond®

Engineering Adhesives

SAFETY DATA SHEET

Permabond TA4210B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permabond TA4210B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Permabond Engineering Adhesives Ltd.
Wessex Way
Colden Common
Winchester
Hampshire SO21 1WP
United Kingdom
Tel: +44 (0)1962 711 661
Fax: +44 (0)1962 711 662
info.europe@permabond.com

1.4. Emergency telephone number

Emergency telephone CHEMTREC UK: +(44)-870-8200418 CHEMTREC US: 800-424-9300 (CCN: 829878)

National emergency telephone number CHEMTREC Ireland: +(353)-19014670
CHEMTREC Australia: +(61)-290372994
CHEMTREC New Zealand: +(64)-98010034

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)


Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

Permabond TA4210B

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352a IF ON SKIN: Wash with plenty of soap and water</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308+P313 IF exposed or concerned: Get medical advice/ attention.</p>
Contains	METHYL METHACRYLATE, 2-HYDROXYETHYL METHACRYLATE
Supplementary precautionary statements	<p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/container in accordance with existing Community, National and local regulations.</p>

2.3. Other hazards

None under normal conditions. This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

METHYL METHACRYLATE 30-60% CAS number: 80-62-6 EC number: 201-297-1 REACH registration number: 01-2119452498-28-XXXX
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Skin Sens. 1 - H317 STOT SE 3 - H335
2-HYDROXYETHYL METHACRYLATE 10-30% CAS number: 868-77-9 EC number: 212-782-2 REACH registration number: 01-2119490169-29-XXXX
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Permabond TA4210B

3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-PROPYLPYRIDINE	1-5%
CAS number: 34562-31-7 EC number: 252-091-3 REACH registration exemption – < 1 tonne	
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. If symptoms develop, obtain medical attention
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Irritating to respiratory system.
Skin contact	Skin irritation. Mild dermatitis, allergic skin rash.
Eye contact	Irritating and may cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. Treat symptomatically.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Flammable liquid and vapour. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.
Hazardous combustion products	Burning produces irritating, toxic and obnoxious fumes. Carbon monoxide, carbon dioxide, and unknown hydrocarbons. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

5.3. Advice for firefighters

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

Permabond TA4210B

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Eliminate all sources of ignition. Ensure adequate ventilation of the working area. Do not breathe vapour. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for disposal.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Use in a well ventilated area. Do not ingest or inhale. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep container tightly closed, in a cool, well ventilated place. Keep container dry. Store in closed original container at temperatures between 2°C and 7°C.

7.3. Specific end use(s)

Specific end use(s) Adhesive.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

METHYL METHACRYLATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³

WEL = Workplace Exposure Limit

METHYL METHACRYLATE (CAS: 80-62-6)

DNEL Workers, Industry/Professional - Inhalation; Long term : 208 mg/m³
Workers, Industry/Professional - Dermal; Long term : 13.67 mg/kg/day
Workers, Industry/Professional - Inhalation; Short term : 416 mg/m³

PNEC Workers, Industry/Professional - Water; Long term <0.94 mg/l

2-HYDROXYETHYL METHACRYLATE (CAS: 868-77-9)

DNEL Workers, Industry - Inhalation; Long term systemic effects: 4.9 mg/m³
Workers, Industry - Dermal; Long term systemic effects: 1.3 mg/kg/day

Permabond TA4210B

PNEC	Workers, Industry - Water; Long term 0.482 mg/l
	Workers, Industry - Soil; Long term 0.476 mg/kg
	Workers, Industry - STP; Long term 10 mg/l
	Workers, Industry - Fresh water; 3.79 mg/kg

3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-PROPYLPYRIDINE (CAS: 34562-31-7)

DNEL	No data available.
PNEC	No data available.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield. Personal eye protection should conform to EN 166

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn. Gloves should conform to EN 374. For exposure up to 4 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 0.5 hours. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.4 mm The selected gloves should have a breakthrough time of at least 8 hours. The breakthrough time for any glove material may be different for different glove manufacturers. The most suitable glove should be chosen in consultation with the glove supplier/manufacture, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Other skin and body protection

Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke. Use of good industrial hygiene practices is required.

Respiratory protection

Ensure adequate ventilation of the working area. Respiratory protection may be required if excessive airborne contamination occurs. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Organic vapour filter. Type A. (EN14387)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	Off-white.
Odour	Pungent. Acrylic
Odour threshold	Not available.

Permabond TA4210B

pH	Not relevant.
Melting point	Not available.
Initial boiling point and range	~100°C
Flash point	11°C
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	≈28 mm Hg
Vapour density	≈3.46
Relative density	1.0
Solubility(ies)	Slightly soluble in water. Soluble in the following materials: Organic solvents.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Viscosity	≈45000 mPa s @ 23°C Thixotropic
Oxidising properties	Not available.

9.2. Other information

Other information Not relevant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react with the product: Strong oxidising agents. Strong acids. Strong alkalis.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Take precautionary measures against static discharges. Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Strong alkalis.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified organic compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Permabond TA4210B

Toxicological effects The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Skin sensitisation

Skin sensitisation May cause sensitisation by skin contact.

Aspiration hazard

Aspiration hazard None under normal conditions.

Inhalation May cause respiratory system irritation.

Skin contact Irritating to skin.

Eye contact Irritating and may cause redness and pain.

Toxicological information on ingredients.

METHYL METHACRYLATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,000.0

Species Rat

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 29.8

Species Rat

Skin corrosion/irritation

Skin corrosion/irritation Not irritating. Prolonged skin contact may cause temporary irritation.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Respiratory sensitisation

Respiratory sensitisation Mouse: Sensitising.

Skin sensitisation

Skin sensitisation Local Lymph Node Assay (LLNA) - Mouse: Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Inconclusive.

Genotoxicity - in vivo This substance has no evidence of mutagenic properties.

Carcinogenicity

Permabond TA4210B

Carcinogenicity	CMR: no
IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No evidence of reproductive toxicity in animal studies.
Reproductive toxicity - development	No evidence of reproductive toxicity in animal studies. non-teratogenic, not embryotoxic
<u>Specific target organ toxicity - single exposure</u>	
Target organs	Respiratory tract Irritation.
<u>Specific target organ toxicity - repeated exposure</u>	
Target organs	No specific target organs known.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.

2-HYDROXYETHYL METHACRYLATE

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	5,000.0
Species	Rat
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	5,000.0
Species	Rabbit
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC₅₀)	No information available.
<u>Skin corrosion/irritation</u>	
Animal data	Erythema/eschar score: Very slight erythema - barely perceptible (1). Not irritating.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Moderately irritating.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	No information available.
<u>Skin sensitisation</u>	
Skin sensitisation	Guinea pig maximization test (GPMT) - Guinea pig: Sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Conclusive data but not sufficient for classification.
Genotoxicity - in vivo	Chromosome aberration: Negative.
<u>Carcinogenicity</u>	
Carcinogenicity	No specific test data are available.

Permabond TA4210B

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOAEL \geq 1000 mg/kg/day, Oral, Rat F1

Reproductive toxicity - development Developmental toxicity: - NOAEL: \geq 1000 mg/kg/day, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure No specific test data are available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No specific test data are available.

Aspiration hazard

Aspiration hazard Not applicable.

3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-PROPYLPYRIDINE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 500.1

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 1,000.1

Species Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No specific test data are available.

Skin corrosion/irritation

Skin corrosion/irritation Moderately irritating.

Serious eye damage/irritation

Serious eye damage/irritation Moderately irritating.

Respiratory sensitisation

Respiratory sensitisation May cause respiratory system irritation.

Skin sensitisation

Skin sensitisation No specific test data are available.

Germ cell mutagenicity

Genotoxicity - in vitro No specific test data are available.

Carcinogenicity

Carcinogenicity No specific test data are available.

Reproductive toxicity

Reproductive toxicity - fertility No specific test data are available.

Specific target organ toxicity - single exposure

Permabond TA4210B

STOT - single exposure No specific test data are available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No specific test data are available.

Aspiration hazard

Aspiration hazard No specific test data are available.

SECTION 12: Ecological information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Toxicity The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Ecological information on ingredients.

METHYL METHACRYLATE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: > 79 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 69 mg/l, Daphnia magna

Acute toxicity - aquatic plants NOEC, 72 hours: > 110 mg/l, Selenastrum capricornutum
EC₅₀, 72 hours: > 100 mg/l, Selenastrum capricornutum

Acute toxicity - microorganisms EC₂₀, 30 minutes: 150 - 200 mg/l, Activated sludge

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOEC, 35 days: 9.4 mg/l, Danio rerio (Zebrafish)

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 37 mg/l, Daphnia magna

2-HYDROXYETHYL METHACRYLATE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: > 100 mg/l, Oryzias latipes (Red killifish)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 380 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 836 mg/l, Selenastrum capricornutum
NOEC, 72 hours: 400 mg/l, Selenastrum capricornutum

Acute toxicity - microorganisms EC₅₀, 16 hours: > 3000 mg/l, Pseudomonas fluorescens

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 24.1 mg/l, Daphnia magna

Permabond TA4210B

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

Ecological information on ingredients.

METHYL METHACRYLATE

Biodegradation Water - Degradation 94%: 14 days

2-HYDROXYETHYL METHACRYLATE

Biodegradation Water - Degradation 84%: 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

2-HYDROXYETHYL METHACRYLATE

Bioaccumulative potential BCF: 1.34 - 1.54,

12.4. Mobility in soil

Mobility No data available. The product has poor water-solubility.

Ecological information on ingredients.

2-HYDROXYETHYL METHACRYLATE

Adsorption/desorption coefficient Water - Koc: 42.7 @ 20°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste disposal should be in accordance with existing Community, National and local regulations Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances.

SECTION 14: Transport information

14.1. UN number

1993

14.2. UN proper shipping name

Permabond TA4210B

FLAMMABLE LIQUID, N.O.S. (contains Methylmethacrylate)

14.3. Transport hazard class(es)

3

Transport labels



14.4. Packing group

II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-E

Hazard Identification Number (ADR/RID) 33 Highly flammable liquid (flash point below 21°C).

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Guidance Workplace Exposure Limits EH40.
CHIP for everyone HSG228.
Safety Data Sheets for Substances and Preparations.
Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 07/08/2019

Revision 7

Supersedes date 25/02/2019

Permabond TA4210B

Hazard statements in full	H225 Highly flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.
----------------------------------	--

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.